



ZHEJIANG UNIU-NE Technology CO., LTD

浙江宇力微新能源科技有限公司



U6119S/SA/SC Data Sheet

V 3.2

版权归浙江宇力微新能源科技有限公司

DC-DC CONVERTER CONTROL CIRCUITS

General Description

The U6119S/SA/SC series is a monolithic control circuit delivering the main functions for DC-DC voltage converting.

The device contains an internal temperature compensated reference, comparator, duty cycle controlled oscillator with an active current limit circuit, driver and high current output switch. Output voltage is ADJ Vol, NO-integrated two external resistors with a 2% reference accuracy.

Employing a minimum number of external components the U6119S/SA/SC devices series is designed for Step-Down applications.

Packages



Key Features

- VIN 200V/100V MOS
- Output Switch ADJ
- 2% Reference Accuracy
- Low Quiescent Current: 15μA(TYP.)
- Out MOSFET Frequency Operation To 200KHZ
- Active Current Limiting
- Support Flyback and Buck Topology QR-Buck CC Control (SEL=GND)
- Low Standby Power < 70mW
- Programmable Cable Drop Compensation: (CDC) in PSR CV Mode
- Built-in AC Line & Load CC Compensation
- Built in Protections:
 - Short Load Protection (SLP)
 - On-Chip Thermal Shutdown (OTP)
 - Cycle-by-Cycle Current Limiting
 - Leading Edge Blanking (LEB)
 - Pin Floating Protecting
- VDD UVLO OVP & Clamp
- Package (SOP7)

Applications

- Electric-Vehicle, Electric-Bicycle
- Appliance
- Industry Controls




Products Information

Base Part Number	Package Type	Rsdon		V _{OFFSET}
		Min(ohm)	Max(ohm)	
U6119S	SOP7	0.75	0.85	200V
U6119SA	SOP7	0.1	0.15	100V
U6119SC	SOP7	0.1	0.15	100V

Order Information

Number	DESCRIPTION
U6119SC	SOP-7, Halogen-free, Tape & Reel, 3000Pcs/Reel
U6119S/SA	SOP-7, Halogen-free, Tape & Reel, 3000Pcs/Reel

Typical Application Circuit



Absolute Maximum Ratings

Symbol	Parameter	Value	Unit
V_{dd}	Power Supply Voltage	26	V
V_{ir}	Comparator Input Voltage Range	-0.3 to 20	V
I_{ds}	Driver Drain Current	1/1.5	A
I_{sw}	Switch Current	3/5	A
P_{tot}	Power Dissipation at $T_{amb} = 25^{\circ}\text{C}$ (for SOIC Package)	0.625	W
T_{op}	Operating Ambient Temperature Rang(for AC SERIES)	-40 to 145	$^{\circ}\text{C}$
	Operating Ambient Temperature Rang(for AB SERIES)	-40 to 145	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Rang	-40 to 150	$^{\circ}\text{C}$

1:Absolute Maximum Rating are those values beyond which damage to the device may occur.

2:Functional operation under these condition is not implied.

Electrical Characteristics

(Refer to the test circuits, $V_{CC} = 60\text{V}$, $T = T_{LOW}$ to T_{HIGH} , unless otherwise specified, see note 2)

Control Function Section						
T_{LEB}	Current Sense Leading Edge Blanking Time	(Note 2)	—	200	—	ns
T_{on_min}	Minimum On Time	(Note 2)	—	300	—	ns
T_{on_max}	Maximum On Time		10	12	14	us
T_{ss}	Internal Soft Start Time	(Note 2)	—	5	—	ms
F_{clk}	Internal Frequency Clock		—	ADJ	200	kHz
ΔF_{clk}	Peak to Peak Frequency Jitter		—	10	—	kHz
BV_{DSS}	MOSFET Break Down Voltage		—	200/100	—	V
Over Temperature						
T_{SD}	Thermal Shut Down	(Note 2)	—	140	—	$^{\circ}\text{C}$
T_{RC}	Thermal Recovery	(Note 2)	—	130	—	$^{\circ}\text{C}$

Note1.Stresses listed as the above "Maximum Ratings" may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to maximum rating conditions for extended periods may remain possibility to affect device reliability.

Note2.It's guaranteed by design and functionally tested during production manufacture.

Peration Description

Over Temperature Protection

When the IC temperature is over 140℃, the IC shuts down. Only when the IC temperature drops to 80℃, the IC restarts to work.

Light Load Mode Operation

To save more power loss in no load condition, U6119S/SA/SC family adopts a light load mode operation. When the switching period is longer than 300us, the peak current limit will be decreased to 100mA. With this feature, ultra no load power loss consumed by the pre-load can be <5mW.

The Selection of the DC Out put Stage

The output power rage determines the selection of the CS and LX design. For Pout<4W, it's recommended to use CV rectification; for Pout>4W, it's recommended to use CC rectification.

Components Selection

Start-Up Resistor (R_{ST}) and Hold-up Capacitor (C_{VIN})

To keep proper start-up operation and meet the start-up time requirement, the value of the V_{IN} capacitor C_{VIN} and start-up resistor R_{ST} need well designed.

Firstly make sure the current flowing through the R_{ST} is larger than the IC start-up current I_{VIN_ST} (3uA typically) and lower than the IC operation current I_{VIN_op} (800uA typically).

$$\frac{V_{in_max}}{I_{VIN_op}} < R_{ST} < \frac{V_{in_min}}{I_{VIN_ST}}$$

V_{in_min}: The minimum peak value of DC input voltage.

V_{in_max}: The maximum peak value of DC input voltage. For universal input, V_{in_max} is 180V.

Secondly the VIN capacitor is recommended to be selected by the following equation:

$$C_{VIN} < \frac{\left(\frac{V_{in_min}}{R_{ST}} - I_{VIN_ST}\right) \cdot T_{ST}}{V_{IN_ON}}$$

For better line and load regulation, the value of C_{VIN} is recommended to be as small as possible. Typically 1uF is recommended. If the VIN capacitance is not big enough to cause the start-up failed; increase the value of C_{VIN} and decrease the R_{ST}, re-do the calculation of above equation until ideal start-up performance is got.

For better noise immunity, it's recommended that the VIN capacitor be placed as close as possible to the VIN Pin.

Quasi Resonant Buck (QR-Buck) Constant Current Control for LED Lighting

If SEL pin is short to GND, U6119S/SA/SC will works in Quasi-Resonant Buck mode. In QR-Buck mode, the IC keeps CS peak current constant and starts new PWM cycle with valley switching. Therefore, high precision CC and high conversion efficiency can be achieved simultaneously. The average output current is given by:

$$I_{Buck_CC_OUT}(mA) \cong \frac{1}{2} \times \frac{500mV}{R_{cs}(\Omega)}$$

Freewheeling Diode (D₁)

Diode D1 should be an ultra-fast type. Slow diode is not acceptable, because the inductor is always working in continuous conduction mode during start-up period. Slow diode will cause high current spike which will falsely make the Power MOSFET turned off and prevent the output voltage reach regulation. Slow diode will also cause extra power loss and make the efficiency lower down. A 100V/1A diode with recovery time <50ns is recommended for Buck converter and 200V/A diode with recovery time <50ns is recommended for Buck/Boost converter, such as ES1D and ES2D.

Feedback Diode (D_F)

The information of the output voltage is sent the IC through the diode DF which can be a slow diode, such as 1N400X series. To minimize the output voltage error, the forward voltage of D1 and DF should match. At the same time, the power supply of the IC will be taken place by the output voltage through DF after the soft-start.

Inductor (L)

For Buck converter, the selection of L can be calculated by the following equation:

$$L = \frac{2 \cdot (V_{in_max} - V_{DS} - V_o) \cdot V_o \cdot I_o}{\eta \cdot [I_{limit}^2 - (2 \cdot I_o - I_{limit})^2] \cdot (V_{in_min} - V_{DS}) \cdot f_{sw}} \quad \text{for CCM}$$

$$L = \frac{2 \cdot (V_{in_max} - V_{DS} - V_o) \cdot V_o \cdot I_o}{\eta \cdot I_{limit}^2 \cdot (V_{in_min} - V_{DS}) \cdot f_{sw}} \quad \text{for DCM}$$

For Buck/Boost converter, the selection of L can be calculated by the following equation:

$$L = 2 \cdot \frac{P_o}{\eta \cdot [I_{limit}^2 - (2 \cdot I_o - I_{limit})^2] \cdot f_{sw}} \quad \text{for CCM}$$

$$L = 2 \cdot \frac{P_o}{\eta \cdot I_{limit}^2 \cdot f_{sw}} \quad \text{for DCM}$$

Where:

When $I_o > I_{limit}/2$, it's working in CCM operation mode;

when $I_o < I_{limit}/2$, it's working in DCM operation mode.

V_{in_min} : The minimum DC input voltage after the rectified diode bridge. It's recommended to keep

V_{in_min} higher than 70V always.

η : The overall estimated efficiency, the typical value of 0.8 is recommended for DCM and 0.7 for CCM.

V_o : The averaged output voltage.

I_o : The averaged output current.

V_F : The forward conduction voltage of the freewheeling diode D1.

V_{DS} : The MOSFET conduction voltage during it's turned on. The typical value of 5V is recommended

f_{sw} : The switching frequency and 56 kHz is recommended.

I_{limit} : The minimum peak inductor current limit.

Any standard off-the-shelf inductor that meets the design requirement can be selected. The value of the inductor L determines the averaged switching frequency according to the rule of power balance. Typically a 0.68mH-22uH inductor is recommended to be used with $I_{sat} > 0.6A$

Output Capacitor (C_{OUT})

The selection of output capacitor is determined by the requirement of the output voltage ripple. To make the output ripple small enough, a large value of C_{OUT} is needed. But large value of C_{OUT} will increase the cost and need longer time for soft-start. Typically a capacitor with 220uF/25V is recommended.

Pre-Load Resistor (R_L)

At no load condition, the switching frequency is determined by the value of C_{VIN} and the operation current of the IC not by the output voltage information. Combined with the value of the selection of inductor L1, there's a minimum input power for this circuit. To keep the regulation of the output voltage at no load condition, a minimum load current is needed. For 15V application, a resistor with value around of 30k ohm is recommended.

Table 1 shows the relationship between these circuit parameters and the key operation performance.

Table 1

	Start-up Time	Output Ripple	No Load
R _{ST} ↑	↑	→	↓
C _{VIN} ↑	↑	↑	↓
L ↑	↓	↑	↑
C _{OUT} ↑	↑	↓	→

Programmable Cable Drop Compensation (CDC) in CV Mode

In smart phone charger application, the battery is always connected to the adapter with a cable wire which can cause several percentages of voltage drop on the actual battery voltage. In U6119S/SA/SC, an offset voltage is generated at FB pin by an internal current source (modulated by CDC block, as shown in Fig.5) flowing into the resistor divider. The current is proportional to the switching period, thus, it is inversely proportional to the output power P_{out}. Therefore, the drop due the cable loss can be compensated. As the load decreases from full loading to zero loading, the offset voltage at FB pin will increase. By adjusting the resistance of R1 and R2 (as shown in Fig.), the cable loss compensation can be programmed. The percentage of maximum compensation is given by:

$$\frac{\Delta V(\text{cable})}{V_{out}} \approx \frac{I_{\text{cable_max}} \times (R1 // R2)}{V_{FB_REF}} \times 100\%$$

For example, R1=3 K Ω , R2=18K Ω , The percentage of maximum compensation is given by

$$\frac{\Delta V(\text{cable})}{V_{out}} = \frac{63\mu A \times (3K // 18K)}{2V} \times 100\% = 8.1\%$$




Fig.5 CDC block

1.版本记录

DATE	REV.	DESCRIPTION
2018/04/19	1.0	First Release
2019/05/21	2.0	Change the package
2020/06/18	3.0	Change the header
2021/10/22	3.2	Layout adjustment

2.免责声明

浙江宇力微新能源科技有限公司保留对本文档的更改和解释权力，不另行通知！客户在下单前应获取我司最新版本资料，并验证相关信息是否最新和完整。量产方案需使用方自行验证并自担所有批量风险责任。未经我司授权，该文件不得私自复制和修改。产品不断提升，以追求高品质、稳定性强、可靠性高、环保、节能、高效为目标，我司将竭诚为客户提供性价比高的系统开发方案、技术支持等更优秀的服务。

版权所有 浙江宇力微新能源科技有限公司/绍兴宇力半导体有限公司

3.联系我们

浙江宇力微新能源科技有限公司

总部地址：绍兴市越城区斗门街道袍渎路25号中节能科创园45幢4/5楼

电话：0575-85087896（研发部）

传真：0575-88125157

E-mail: htw@uni-semic.com

无锡地址:江苏省无锡市锡山区先锋中路6号中国电子(无锡)数字芯城1#综合楼503室

电 话：0510-85297939

E-mail: zh@uni-semic.com

深圳地址:深圳市宝安区西乡街道南昌社区宝源路泳辉国际商务大厦410

电 话：0755-84510976

E-mail: htw@uni-semic.com